

## **F22** 3 Phase Modular UPS

20kVA - 60kVA



The ION F22 is a world class, redundant, scalable, 3 Phase UPS power protection system designed to cost effectively provide high levels of availability. The ION F22 is a true modular system. Made up of dedicated and redundant 20kVA power modules and batteries, all engineered into a design that is easily and efficiently serviceable, this solution can scale power and runtime as demand grows or as higher levels of availability are required from 20kVA to 60kVA. The ION F22 simplifies maintenance and replacement with low MTTR.











## F22 FEATURES

- 2 year warranty\*
- Online double conversion technology
- Modular hot swappable battery packs
- Battery monitoring system
- Integrated IGBT module with improved performance
- Large Friendly touch LCD with graphic display
- High efficiency of 98% in ECO mode
- High power density compact 20kVA power modules

## **F22**3 Phase Modular UPS

Specifications

|                                |                 | F22-60-20M   |
|--------------------------------|-----------------|--|
| Output                         |                 |  |
| Output Power Capacity          |                 | 54kW/60kVA   |
| Max Configurable Power (Watts) |                 | 54kW/60kVA   |
| Power Module Capacity          |                 | 18kW/20kVA   |
| Voltage Regulation             |                 | ±1% (Balance load); ±1.5% (Unbalance load)                               |
| THDu                           |                 | THD<1.5% (linear load ), THD<5% (None linear load)                       |
| Power Factor                   |                 | 0,9  |
| Crest Ratio                    |                 | 3:01   |
| Overload Capacity              |                 | 110% for 1 hour; 125% for 10 minutes ;150% for 1 minute; >150% for 200ms |
| Input                          | ,               |  |
| Phase                          |                 | 3 Ph + Neutral + Ground, 380V/400V/415V (line to line)                   |
| Voltage Range                  |                 | -45%   |
| Frequency Range                |                 | 40Hz-70Hz  |
| Power Factor                   |                 | >0.99  |
| THDi                           |                 | THDi<3% @100% linear load  |
| Battery                        |                 |  |
| Voltage                        |                 | ±240VDC  |
| Charge Power                   |                 | 20%*System Power   |
| Charge Voltage Precision       |                 | ±1%  |
| System                         |                 |  |
| System Efficiency              |                 | Normal mode: 95%; ECO mode: 98%;   |
|                                |                 | Battery mode: 95%  |
| Display                        |                 | LCD+LED, Touch Screen+Keyboard   |
| IP Class                       |                 | IP20   |
| Interface (Communication port) |                 | Standard:RS232, RS485, Dry contacts;                                     |
|                                |                 | Optional: SNMP   |
| Installation/Connection        |                 | Top or bottom cable connection   |
| Operation/Storage Temperature  |                 | 0-40° <b>C</b> /-40-70° <b>C</b>   |
| Relative Humidity              |                 | 0-95% (non-condensing)   |
| Noise                          |                 | 55dB (1 meter away)  |
| Physical                       |                 |  |
| ,                              | Cabinet         | 205Kg  |
| Weight                         | Power module    | 22Kg   |
|                                | Battery package | 10kg (without battery)   |
|                                | Cabinet         | 600*1020*2000mm  |
| Dimension W*D*H                | Power module    | 440*590*134mm  |
|                                | Battery package | 120*824*177mm  |
| Conformance                    | 71 0-           |  |
| Approvals                      |                 | CE   |
|                                |                 | 2 Year Manufacturer's Warranty*  |
| Standard warranty              |                 | Z fear Manufacturer 5 Warranty   |

<sup>\*</sup>Product specifications are subject to change without further notice.

<sup>\*2</sup> year warranty on UPS electronics and batteries please refer to the ION website for more information