

www.ionups.com.a

## **PDU**Power Distribution

Basic / Metered / Switched y Outlet



ION have a large range of basic, metered and switched by outlet Power Distribution Units (PDUs) that have been designed to meet the needs of the modern IT and commercial industries. Compatible with any UPS system, they create an easy platform to support multiple pieces of equipment.



## **PDU** FEATURES

- 3 Year Advanced Replacement Warranty\*
- Reliable Power Distribution for IT Equipment
- Range of options from basic, metered and switched by outlet
- Variety of power metering and control options
- Network-grade plugs and outlets
- Ruggedized industrial-grade metal enclosures

## **PDU**Power Distribution

## Specifications

Part Number	Rating	Function	RU	Input	Output	Dimensions: L x W x H
Basic PDU						
B-12U1	10 Amp	Basic	1	C14	(12) C13	482 x 66 x 44.4 mm
B-16U0	16 Amp	Basic	0	C20	(16) C13	1100 x 56 x 52 mm
B-204U0	16 Amp	Basic	0	C20	(20) C13, (4) C19	1500 x 56 x 52 mm
Metered PDU						
M-12U1	10 Amp	Metered	1	C14 (3m cable)	(12) C13	482.6 × 216 × 44.4 mm
M-84U1	16 Amp	Metered	1	C20 (3m cable)	(8) C13, (4) C19	482.6 × 216 × 44.4 mm
M-204U0	16 Amp	Metered	0	C20	(20) C13, (4) C19	1800 x 56 x 52 mm
M-204U032	32 Amp	Metered	0	IEC309-32A (3m cable)	(20) C13, (4) C19	1800 x 56 x 52 mm
Switched By Outlet PDU						
S-12U1	10 Amp	Switched (by Outlet)	1	C14 (3m cable)	(12) C13	842.6 × 216 × 44.4 mm
S-213U0	16 Amp	Switched (by Outlet)	0	C20 (3m cable)	(21) C13, (3) C19	1800 x 56 x 52 mm
S-213U032	32 Amp	Switched (by Outlet)	0	IEC309-32A (3m cable)	(21) C13, (3) C19	1800 x 56 x 52 mm

	Connection guide		
Input	10Amp		
(1,3)	C14 (IEC-320-C14)		
Input	16Amp		
	C20 (IEC-320-C20)		
Input	32Amp		
	32A-309 (IEC-309-32A)		
Output	10Amp		
	C13 ( IEC-320-C13)		
Output	16Amp		
	C19 (IEC-320-C19)		

<sup>\*</sup>Product specifications are subject to change without further notice.

<sup>\*3</sup> Year advanced replacement warranty in please refer to the ION website for more information